SOFTWARE TOOL ARTICLE

BridgeDb app: unifying identifier mapping services for Cytoscape [version 1; peer review: 2 approved]

Jianjiong Gao¹, Chao Zhang², Martijn van Iersel³, Li Zhang⁴, Dong Xu⁵, Nikolaus Schultz^{1,6}, Alexander R. Pico⁷

¹Kravis Center for Molecular Oncology, Memorial Sloan Kettering Cancer Center, New York, NY 10065, USA

²Institute for Computational Biomedicine, Weill Cornell Medical College, New York, NY 10065, USA

³General Bioinformatics, Reading, Birkshire, RG4 7RT, UK

⁴School of Computer Science and Engineering, Changchun University of Technology, Changchun, 130012, China

⁵Department of Computer Science, C.S. Bond Life Sciences Center, University of Missouri, Columbia, MO 65211, USA

⁶Department of Epidemiology and Biostatistics, Memorial Sloan Kettering Cancer Center, New York, NY 10065, USA

⁷Gladstone Institutes, San Francisco, CA 94158, USA

V1 First published: 01 Jul 2014, 3:148
<https://doi.org/10.12688/f1000research.4521.1>

Latest published: 01 Jul 2014, 3:148
<https://doi.org/10.12688/f1000research.4521.1>

Abstract

The BridgeDb app for Cytoscape allows users to map and annotate identifiers of genes, proteins and metabolites in the context of biological networks. The app greatly simplifies the identifier mapping process in Cytoscape by providing a unified interface to different mapping resources and services. The app also provides a programming interface via Cytoscape Commands that can be utilized for identifier mapping by other Cytoscape apps. In this article we provide a technical guide to the BridgeDb app for mapping identifiers in Cytoscape.

This article is included in the **Cytoscape** gateway.

This article is included in the **Bioinformatics** gateway.

Open Peer Review

Approval Status

	1	2
version 1
01 Jul 2014	view	view

1. **Benno Schwikowski**, Institut Pasteur, Paris, France

2. **Olivier Elemento**, Weill Cornell Medical College, New York, NY, USA

Any reports and responses or comments on the article can be found at the end of the article.

Corresponding author: Jianjiong Gao (jianjiong.gao@gmail.com)

Competing interests: No competing interests were disclosed.

Grant information: This work was partially funded by the Google Summer of Code program (JG, CZ, and LZ), the Robertson Foundation (NS), and by NIGMS R01-GM100039 (ARP).

The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

Copyright: © 2014 Gao J *et al.* This is an open access article distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited. Data associated with the article are available under the terms of the [Creative Commons Zero "No rights reserved" data waiver](#) (CC0 1.0 Public domain dedication).

How to cite this article: Gao J, Zhang C, van Iersel M *et al.* **BridgeDb app: unifying identifier mapping services for Cytoscape** [version 1; peer review: 2 approved] F1000Research 2014, 3:148 <https://doi.org/10.12688/f1000research.4521.1>

First published: 01 Jul 2014, 3:148 <https://doi.org/10.12688/f1000research.4521.1>

Introduction

Cytoscape¹ is a powerful network visualization tool and platform for data integration and analysis. However, identifier mapping remains a challenge when working with biological data from different sources. We developed the BridgeDb app for Cytoscape to provide utilities for mapping and annotating identifiers in the network context. Built on the BridgeDb open-source framework for identifier mapping², the BridgeDb app provides a graphical user interface (GUI) for users and a command interface for other Cytoscape apps to perform identifier mapping in Cytoscape networks. As a result, BridgeDb enables or simplifies the processes of identifier translation, biological entity unification, and functional annotation.

Implementation

The BridgeDb identifier mapping framework (<http://bridgedb.org/>)² was designed to provide standardized access to gene, protein and metabolite identifier mapping services such as Ensembl BioMart³, Synergizer⁴, PICR⁵ and BridgeDb web services and BridgeDb database files. By creating a Java-based abstract layer, BridgeDb enables bioinformatics applications to connect to different mapping resources through the same interface, which greatly alleviates the burden of exploring, maintaining and switching between resources.

Built upon BridgeDb framework and API, the BridgeDb app for Cytoscape can be used to connect to different mapping resources and map identifiers in Cytoscape networks. The BridgeDb app was implemented based on the Cytoscape 3 API. Its predecessor was the CyThesaurus plugin for Cytoscape 2. To take advantage of the new OSGi based architecture in Cytoscape 3 and its clearly defined and simplified API, we have rewritten the CyThesaurus plugin into an OSGi bundle app. Figure 1 illustrates the implementation details. The identifier mapping API of BridgeDb framework was wrapped by Cytoscape *Task* and *TaskFactory* API, which provide identifier mapping utilities to users through graphical user interfaces for managing mapping resources and performing identifier mapping. The BridgeDb app Tasks were also registered to Cytoscape as command services allowing other apps, such as Mosaic⁶ and NOA⁷ apps, and the Merge Network tool, to take advantage of BridgeDb app's identifier mapping capacities.

Results

BridgeDb app user interface

The BridgeDb app provides an intuitive GUI to perform identifier mapping in Cytoscape networks, consisting of two interactive dialogs for resource management and identifier mapping, respectively, which can be opened via the menu item Apps/BridgeDb.

The resource management dialog allows user to add, remove, and select or deselect mapping resources. Once the resources are configured, they will be saved in a global property file and therefore shared among different Cytoscape sessions. Currently BridgeDb app supports local and remote delimited text files, BridgeDb database files, BridgeDb web service, BioMart web service, and Synergizer web service. Web services are easy to access and up to date and therefore are preferable for annotating small to medium-size networks (less than 1,000 nodes). It is highly recommended to download and use the BridgeDb database files for mapping identifiers in large networks in order to save time. Local delimited text files

Figure 1. BridgeDb app implementation.

are useful when mapping between non-standard or customized identifiers. To avoid ambiguity, it is recommended to select only one resource unless multiple resources are believed to be complementary to each other. Particularly, resources for different species should not be selected at the same time. Database or text files are also preferable when reproducibility is essential. We will update the app to support more mapping resources as BridgeDb API keeps being developed.

The identifier mapping dialog is the main interface for mapping identifiers stored in the node table in the selected Cytoscape network. The user needs to choose the source identifier types, columns in the node table that contain the source identifiers, target identifier types, and columns to save the target identifiers. When mapping, all specified source identifier types in all selected resources will be queried for matching identifiers. If one source identifier can be mapped onto multiple target identifiers, all target identifiers can be saved as a list in the node table. If a target column exists in the node table, all values in the column will be overwritten with the target identifiers; otherwise, a new column will be created and filled with the target identifiers. Besides a set of supported identifier types (e.g., Entrez Gene ID and UniProt accession), a mapping resource such as BridgeDb database may also have a set of supported attributes (e.g., gene symbol and description).

BridgeDb app command interface

The BridgeDb app also provides a set of Cytoscape commands, which can be used by scripting or by other Cytoscape apps (client apps) to take advantage of the identifier mapping capacities provided by BridgeDb app. **Table 1** provides a selected list of commands supported by BridgeDb. Every command has an optional argument 'appName' in order to allow every client app to have its own set of identifier mapping resources. Morris *et al.* (**setsApp**⁸, *published together in the Cytoscape App collection*⁹) provided an example of how to use commands in client apps.

Example use cases

Use cases of BridgeDb app include identifier translation, biological entity unification, and functional annotation in Cytoscape networks. **Box 1** provides an example of how to use BridgeDb app to facilitate annotation and integration of networks from public databases. In particular, this example shows the steps to generate a *TP53* interaction network by merging networks from different sources using BridgeDb app and Merge Network tool. **Figure 2** illustrates the process of the Cytoscape app NOA⁷ annotating Cytoscape networks with Gene Ontology by utilizing BridgeDb app's command services.

Table 1. Selected BridgeDb app commands. Arguments with asterisks (*) are required.

Command	Arguments	Description
bridgedb resource add	classPath =IDMapper class path* connString =BridgeDb connection string* displayName =display name appName =name of client Cytoscape app	Add a mapping resource. appName is the name of the client Cytoscape app that is using this command.
bridgedb resource remove	connString =BridgeDb connection string* appName =name of Cytoscape app	Remove a mapping resource.
bridgedb resource select	connString =BridgeDb connection string* select =true or false appName =name of client Cytoscape app	Select or deselect an mapping resource.
bridgedb id mapping	network =Cytoscape network name* sourceColumn =source column in node table* targetColumn =source ID type* sourceIdType =target column in node table* targetIdType =target ID type* appName =name of client Cytoscape app	Map identifiers from a column in node table to another in a Cytoscape network.
bridgedb resource config dialog	appName =name of client Cytoscape app	Open the resource management/configuration dialog.
bridgedb main dialog	appName =name of client Cytoscape app	Open the main BridgeDb app dialog.

Box 1. Example: Using BridgeDb app for merging TP53 interaction networks from different sources

1. Install and start Cytoscape 3.1.0 or above
2. Select **File > Import > Network > Public Databases. . .**
3. Enter search condition **TP53 AND human**, press **Search**, select database **IntAct**, and click **Import**
4. After importing, click **No** when asking about whether to manually merge networks, and close the import dialog
5. If needed, install BridgeDb from **Apps > App Manager**
6. Select **File > Import > Network > URL. . . > Example:Human Protein-Protein: Rual et al. . . . Nature 2005**
7. Use default when asking about setting of the new network
8. Select **Apps > BridgeDb > Manager ID Mapping Resources**
9. Click **Databases**, Select database type **.bridge**
10. Click **Download**, download **Hs_Derby_[date].zip**, and unzip the file
11. In Cytoscape, select the unzipped .bridge file
12. Review supported identifier types and click **Close**
13. Select network rual.sif in Network panel

14. Select **Apps > BridgeDb > Map Identifiers**
15. Select **name** as the **Source Column in Node Table**
16. Select **Entrez Gene** as **Source ID Type(s)**
17. Select **Uniprot/TrEMBL** as **Target ID Type**
18. Click **Insert** in the **destination ID types** table
19. Select **Attribute: Symbol** as the second **Target ID Type**
20. Click **OK**, wait, then click **No** to close
21. Search for **TP53** in the Cytoscape search box
22. Select **Select > Nodes > First Neighbors of Selected Nodes > Undirected**
23. Select **File > New > Network > From selected nodes, all edges**
24. Select **Tool > Merge > Networks. . .**
25. Select the network from **IntAct** and **rual.sif(1)**
26. Click **Advanced Network Merge**
27. Select **Matching columns: uniprotkb_accession** for **IntAct**, and **Uniprot/TrEMBL** for **rual.sif(1)**
28. Click **Merge** to get a TP53 interaction network merged from the two sources

Figure 2. NOA app utilizing BridgeDb app services for gene ontology annotation.

Conclusions

In this paper, we presented the BridgeDb app for Cytoscape. By providing a unified interface to various mapping resources, BridgeDb app enables identifier mapping in the network context and therefore greatly eases the process of data integration in Cytoscape.

Software availability

Software available from: <http://apps.cytoscape.org/apps/bridgedb>

Latest source code: <https://github.com/jjgao/bridgedb.cytoscape>

Source code as at the time of publication: <https://github.com/F1000Research/bridgedb.cytoscape>

Archived source code as at the time of publication: <http://www.dx.doi.org/10.5281/zenodo.10465>¹⁰

License: Lesser GNU Public License 2.1: <https://www.gnu.org/licenses/old-licenses/lgpl-2.1.html>

Author contributions

JG, CZ, MI and ARP participated in the design of the described software. JG and MI participated in the development of BridgeDb framework. JG, CZ and LZ implemented the BridgeDb app. JG, CZ, MI, DX, NS and ARP contributed to the development and writing of this article.

Competing interests

No competing interests were disclosed.

Grant information

This work was partially funded by the Google Summer of Code program (JG, CZ, and LZ), the Robertson Foundation (NS), and by NIGMS R01-GM100039 (ARP).

The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

Acknowledgements

We thank Scooter Morris for technical support on command interface, Kristina Hanspers for beta testing, and Gary Bader, Mike Smoot, Keiichiro Ono and David States for providing useful comments.

References

- Shannon P, Markiel A, Ozier O, *et al.*: **Cytoscape: a software environment for integrated models of biomolecular interaction networks**. *Genome Res.* 2003; **13**(11): 2498–2504.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- van Iersel MP, Pico AR, Kelder T, *et al.*: **The BridgeDb framework: standardized access to gene, protein and metabolite identifier mapping services**. *BMC bioinformatics.* 2010; **11**(1): 5.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Kasprzyk A, Keefe D, Smedley D, *et al.*: **EnsMart: a generic system for fast and flexible access to biological data**. *Genome Res.* 2004; **14**(1): 160–169.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Berriz GF, Roth FP: **The Synergizer service for translating gene, protein and other biological identifiers**. *Bioinformatics.* 2008; **24**(19): 2272–2273.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Côté RG, Jones P, Martens L, *et al.*: **The Protein Identifier Cross-Referencing (PICR) service: reconciling protein identifiers across multiple source databases**. *BMC bioinformatics.* 2007; **8**(1): 401.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Zhang C, Hanspers K, Kuchinsky A, *et al.*: **Mosaic: making biological sense of complex networks**. *Bioinformatics.* 2012; **28**(14): 1943–1944.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Zhang C, Wang J, Hanspers K, *et al.*: **NOA: a cytoscape plugin for network ontology analysis**. *Bioinformatics.* 2013; **29**(16): 2066–2067.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Morris JH, Wu A, Doncheva NT, *et al.*: **setsapp: Set operations for cytoscape nodes and edges**. Manuscript submitted for publication. *F1000Research.* 2014.
- The cytoscape app collection**. *F1000Research.* 2014.
- Gao J, Zhang C, van Iersel M, *et al.*: **F1000Research/bridgedb.cytoscape**. *ZENODO.* 2014.
[Data Source](#)

Open Peer Review

Current Peer Review Status:

Version 1

Reviewer Report 22 July 2014

<https://doi.org/10.5256/f1000research.4835.r5522>

© 2014 Elemento O. This is an open access peer review report distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Olivier Elemento

Institute for Computational Biomedicine, Weill Cornell Medical College, New York, NY, USA

The paper by Gao *et al.* describes a Cytoscape app/plugin for cross-database mapping of gene, protein and metabolite identifiers in biological networks. For example, the app can map EntrezGene identifiers to UniProt identifiers for all genes or selected genes in a Cytoscape network. This is an important and useful application that among other application enables the merging of networks obtained from different sources (as shown in demonstration). The app is reasonably user-friendly and intuitive. Most importantly, it does not require any programming knowledge and is accessible via a GUI. I appreciate that it either uses local downloaded files for mapping (for heavy usage) or BridgeDb web services (for smaller networks). The demo in the paper worked flawlessly on my MacBook Air.

Potential future improvements may include ortholog mapping e.g. from mouse to human to enable cross-species network analyses.

Competing Interests: No competing interests were disclosed.

I confirm that I have read this submission and believe that I have an appropriate level of expertise to confirm that it is of an acceptable scientific standard.

Reviewer Report 10 July 2014

<https://doi.org/10.5256/f1000research.4835.r5304>

© 2014 Schwikowski B. This is an open access peer review report distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Benno Schwikowski

Systems Biology Lab, Institut Pasteur, Paris, France

BridgeDB app provides Cytoscape users and app developers with powerful functionality to address the ID mapping problem in integrative data analysis. App user and command interfaces are well-documented; the workflow is functional and recommended for anyone wishing to learn how to use the app.

As a minor suggestion, it would be reassuring to new users if they were able to validate the result of the workflow example in some way.

This is a very useful extension of Cytoscape functionality with broad appeal.

Competing Interests: Our team is co-developer of Cytoscape.

I confirm that I have read this submission and believe that I have an appropriate level of expertise to confirm that it is of an acceptable scientific standard.

The benefits of publishing with F1000Research:

- Your article is published within days, with no editorial bias
- You can publish traditional articles, null/negative results, case reports, data notes and more
- The peer review process is transparent and collaborative
- Your article is indexed in PubMed after passing peer review
- Dedicated customer support at every stage

For pre-submission enquiries, contact research@f1000.com

F1000Research