WEB TOOL

HeatMapView: interactive display of 2D data in biology

[version 1; peer review: 2 approved]

Guy Yachdav¹⁻³, Maximilian Hecht^{1,2}, Metsada Pasmanik-Chor⁴, Adva Yeheskel⁴, Burkhard Rost¹⁻³

¹TUM, Department of Informatics, Bioinformatics & Computational Biology, 5748 Garching/ Munich, Germany

²TUM Graduate School of Information Science in Health (GSISH), 85748 Garching/Munich, Germany

³Biosof LLC, New York, NY, 10001, USA

⁴Bioinformatics Unit, G.S.W. Faculty of Life Sciences, Tel Aviv University, Tel Aviv, 69978, Israel

V1 First published: 13 Feb 2014, 3:48
<https://doi.org/10.12688/f1000research.3-48.v1>

Latest published: 13 Feb 2014, 3:48
<https://doi.org/10.12688/f1000research.3-48.v1>

Abstract

Summary: The HeatMapView is a BioJS component that lays-out and renders two-dimensional (2D) plots or heat maps that are ideally suited to visualize matrix formatted data in biology such as for the display of microarray experiments or the outcome of mutational studies and the study of SNP-like sequence variants. It can be easily integrated into documents and provides a powerful, interactive way to visualize heat maps in web applications. The software uses a scalable graphics technology that adapts the visualization component to any required resolution, a useful feature for a presentation with many different data-points. The component can be applied to present various biological data types. Here, we present two such cases – showing gene expression data and visualizing mutability landscape analysis.

Availability: <https://github.com/biojs/biojs>;
<http://dx.doi.org/10.5281/zenodo.7706>.

This article is included in the BioJS collection.

Open Peer Review

Approval Status

	1	2
version 1
13 Feb 2014	view	view

1. **Jordi Deu-Pons**, University Pompeu Fabra (UPF), Barcelona, Spain

2. **Jon C. Ison**, EMBL European Bioinformatics Institute, Hinxton, Cambridge, UK

Any reports and responses or comments on the article can be found at the end of the article.

Corresponding author: Guy Yachdav (gyachdav@roslab.org)

Competing interests: No competing interests were disclosed.

Grant information: GY and MH are supported by a grant from the Alexander von Humboldt foundation through the German Ministry for Research and Education (BMBF: Bundesministerium fuer Bildung und Forschung).

The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

Copyright: © 2014 Yachdav G *et al.* This is an open access article distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

How to cite this article: Yachdav G, Hecht M, Pasmanik-Chor M *et al.* **HeatMapView: interactive display of 2D data in biology** [version 1; peer review: 2 approved] F1000Research 2014, 3:48 <https://doi.org/10.12688/f1000research.3-48.v1>

First published: 13 Feb 2014, 3:48 <https://doi.org/10.12688/f1000research.3-48.v1>

Introduction

Biological data are often organized into matrices in which the rows signify different items of interest (a gene, a subject, a probe or a position in a sequence), while the columns describe different experiments, variations, or samples. Matrices are easy to process by algorithms. In contrast, the details in large matrices are often, at best, challenging for experts who want to “understand” the data. The information in matrices is usually better digested if presented by 3D plots or heat maps. Heat maps are essentially simplified versions of 3D plots that replace the 3rd dimension with color gradients, thereby conveniently displaying the information contained in matrices. Such heat maps allow for easy visual differentiation between high and low values in a matrix.

Such heat maps are, for example, commonly used to display microarray data as they quickly show which genes (rows) are differentially expressed under some conditions (columns). Microarray technologies utilize arrays of probes located on different exons for each gene and can be helpful in determining gene function by measuring transcription and translation levels under certain experimental conditions. The expression values for the differential expression may be presented at the exon level, correlated with protein domains, and may help to decipher a complex gene expression pattern.

Heat maps can also display the effect of point mutations (single amino acid substitutions, or non-synonymous Single Nucleotide Polymorphisms – nsSNPs). Through the application of methods that predict the impact of mutations¹⁻⁴ we can expand from the view of single variants to the level of sketching the entire *mutability landscape*⁵. This *mutability landscape* is defined by the impact of substituting every residue at each position in a protein by each of the 19 non-native amino acids. The resulting predictions can then be shown in a heat map in order to visualize the impact of each substitution. Regions where mutations have a high average effect (i.e. where almost every substitution is predicted to alter protein function) are especially interesting as these are likely to be of particular and direct importance for protein function.

We developed *HeatMapView* as a BioJS component that can easily be used, reused and, if needed, extended to display matrix data. BioJS⁶ is an open source JavaScript library of components for visualization of biological data on the web. As a JavaScript component, the *HeatMapView* is very flexible, interactive and webready. Previous libraries generating graphical HeatMaps render either static images⁷ or are highly specialized and cannot be reused⁸. To the best of our knowledge, this is the first client-side modular component to visualize matrices that can be integrated into other web applications in a standard manner.

The *HeatMapView* component

HeatMapView uses the D3⁹ JavaScript library to render Scalable Vector Graphics (SVG) objects. SVG technology is now standardized and native to modern web browsers (e.g. Mozilla, Chrome, Safari). The component accepts a simple JSON object containing the data matrix that will be rendered. A secondary JSON object contains configuration directions such as the target DIV element onto which the component will be rendered, the data range to be shown, the color scheme to be used for the component, the size of

the canvas showing the component and the minimum cell size (by default these last two options can be computed automatically).

The *HeatMapView* component automatically renders a heat map based on the input data object and the pre-set color-scheme. Positioning and layout are automatically calculated given the available browser window size. If presenting the entire heat map requires individual cells to be smaller than a given threshold, a secondary panel is automatically rendered to show a zoomed-in version of a local segment in the heat map. This zoom-in panel is presented right under the main heat map panel. The labels for the X-axis and Y-axis are laid out above the top row and next to the left column. The component provides a user control in the form of a frame that can be dragged along the main heat map to determine which area of the heat map should appear in the zoom-in panel. Additionally, a scale bar is presented to show the value ranges and which colors correspond to those values. Finally, each cell in the heat map is associated with a mouse-over event that pops-up tooltips showing the data-value of the cell.

The *HeatMapView* component can be obtained from the BioJS registry at <https://github.com/biojs/biojs>. For users wishing to test the component's capabilities to generate heat map plots for their data without downloading and installing the component, we have set up a server: <http://www.rostlab.org/services/heatmap-viewer>. The server allows users to upload their data in Comma Separated Values (CSV) format and then renders a heat map on the screen. The server also allows exporting the resulting graphics rendering it into an image.

Application use-cases and examples

Eye disease Retinitis Pigmentosa (RP)

The rhodopsin gene encodes a protein of the outer photoreceptor segment that is essential for the visual transduction cascade. Since 1989, many mutations in the rhodopsin gene have been found to be involved in the eye disease Retinitis Pigmentosa (also known as Retinopathia pigmentosa or simply RP¹⁰). RP is a hereditary disease causing retinal degeneration and thereby destroying photoreceptors; this results in severe vision impairment or even blindness.

A typical study of such a hereditary disease might begin with a protocol as follows. According to the UCSC genome browser¹¹, human rhodopsin (RHO, RefSeq: NM_000539.3) consists of 5 exons (located on chr3:129,247,482-129,254,187). The total gene length is 6706 bps (base pairs/nucleotides). The coding region (chr3:129,247,577-129,252,561; i.e. extending over 4985 bps), is translated into a gene-product/protein with 348 residues (UniProt identifier: P08100¹², SwissProt identifier: OPSD_HUMAN¹³). This protein has a single large domain (Pfam identifier: PF00001¹⁴) that is dominated by a “standard” 7-transmembrane receptor region (rhodopsin family), which spans most of the coding region (residues 55 - 306). The human rhodopsin is highly expressed in the heart, liver, skeletal muscle, thyroid and the eye retina.

Viewing gene expression data

It is interesting to locate the array probes intensities on the various protein domain regions. We map the expression profiles of the RHO (from GEO43134) to the structural protein regions through

visualization with the *HeatMapView* component (Figure 1). The different experimental conditions are presented on the rows, while the probes for the RHO gene are shown on the columns, annotated with exon and trans-membrane (TM) location. Probes with high expression are marked in red; those with low expression are colored green. The differences in color of the same probe along the different conditions provides useful information concerning the expression intensity of the various probes, and possible variations in alternative splicing patterns and region conservation across the different samples.

Predicted protein mutability landscape

Since RP is caused by mutations in the rhodopsin gene, researchers have extensively investigated different variations of the gene. Thus, up to now over 100 mutations have been identified and associated with RP. More generally: single nucleotide variations constitute most of the genetic variation among humans and therefore play an important role when studying hereditary diseases or differential drug response. In this context, we show another possible application of the *HeatMapView*, again using the 7TM human rhodopsin (SwissProt identifier: OPSD_HUMAN¹³). The *HeatMapView* provides a fast and easy way to represent high dimensional data in a visually comprehensible way that immediately conveys where mutations are likely to be deleterious. Without using a tool such as the *HeatMapView*, we could hardly obtain an overview of the protein mutability landscape⁵. Mutability landscape studies involve predicting the effect of all possible nsSNPs through computational methods, visualizing the predictions in heat maps and cross-linking these predictions with additional sources of information (such as secondary structure, active sites and correlated mutational behavior). Such regions might highlight important aspects of RP. To this end, heat maps (Figure 2b, 2c) can easily distinguish between low effect

Figure 1. HeatMapView component visualization of microarray expression experiment (Korir et al. 2012; GSE43134). In this experiment, a mutation in a splicing factor that causes Retinitis Pigmentosa (RP) was shown to have an effect on mRNA splicing. Moreover, mutations in the rod photoreceptor-specific protein rhodopsin (RHO) are known to cause RP. Log2 expression values for the 8 probes of human RHO were obtained and located to each of its 5 exons and the 7 trans-membrane (TM) regions (columns). It is interesting to note that the different probes (located on the various regions of RHO), are differentially expressed (high expression colored red and low expression in green). Moreover, we can observe that some RHO probes are expressed differently in the control than in the treatment (case, rows). These results may indicate the effect of the mutated splicing factor on RHO gene in RP disease.

Figure 2. The HeatMapView component displays the mutability landscape of OPSD_HUMAN. Panel a) sketches the secondary structure (helices in red, beta strands in blue). Panel b) shows the predictions of effects for each amino acid substitution. Effects are depicted as color intensities ranging from dark blue (high probability of no or little effect) over white (effect can not be predicted or only with very low reliability) to dark red (high probability of strong effects). Black depicts wildtype residues. The blue box marks the zoomed-in region shown in panel c).

regions (represented in blue) and high effect regions (represented in red) while additional information (such as the secondary structure; Figure 2a) can simply be over-laid. These two components already perfectly convey the information that high effect regions are mainly found in the transmembrane helices and in close proximity of the binding sites. Displaying this simple fact without a heat map would be daunting due to the high dimensionality of the underlying data.

Conclusions

The *HeatMapView* component provides a new, powerful way to generate and display matrix data in web presentations and in publications. The use of scalable graphics enables the rendering of high-resolution images as the interactive nature of the component permits those graphics to be scaled on-demand. Furthermore the component can be applied to different cases highlighting various points of interest from gene expression levels to the effects of mutability on protein function. Finally, to make the *HeatMapView* component widely accessible, we set up a public web server to which users can upload their matrix data and use the resulting code to show an interactive heat map.

Software availability

Zenodo: HeatMap Viewer, doi: [10.5281/zenodo.770615](https://doi.org/10.5281/zenodo.770615)

GitHub: BioJS, <https://github.com/biojs/biojs>

Author contributions

GY developed the original *HeatMapView* component and maintains the *HeatMapView* service. MH contributed the SNP analysis use case. MPC and AY contributed the gene expression data use case. BR contributed the initial idea for the component and helped with its design.

Competing interests

No competing interests were disclosed.

Grant information

GY and MH are supported by a grant from the Alexander von Humboldt foundation through the German Ministry for Research

and Education (BMBF: Bundesministerium fuer Bildung und Forschung).

The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

Acknowledgements

Thanks to Tim Karl and Laszlo Kajan (TUM) for invaluable help with hardware and software; to Marlena Drabik (TUM) for administrative support; to thanks Edda Kloppman and Tatyana Goldberg (TUM) for helpful discussions and invaluable feedback.

References

1. Bromberg Y, Rost B: **SNAP: predict effect of non-synonymous polymorphisms on function.** *Nucleic Acids Res.* 2007; **35**(11): 3823–35.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
2. Bromberg Y, Overton J, Vaisse C, *et al.*: **In silico mutagenesis: a case study of the melanocortin 4 receptor.** *FASEB J.* 2009; **23**(9): 3059–69.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
3. Sunyaev S, Ramensky V, Koch I, *et al.*: **Prediction of deleterious human alleles.** *Hum Mol Genet.* 2001; **10**(6): 591–7.
[PubMed Abstract](#) | [Publisher Full Text](#)
4. Pauline CNg, Steven H: **SIFT: Predicting amino acid changes that affect protein function.** *Nucleic Acids Res.* 2003; **31**(13): 3812–4.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
5. Hecht M, Bromberg Y, Rost B: **News from the protein mutability landscape.** *J Mol Biol.* 2013; **425**(21): 3937–48.
[PubMed Abstract](#) | [Publisher Full Text](#)
6. Gómez J, García LJ, Salazar GA, *et al.*: **BioJS: an open source Javascript framework for biological data visualization.** *Bioinformatics.* 2013; **29**(8): 1103–4 2013.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
7. Pavlidis P, Noble WS: **Matrix2png: a utility for visualizing matrix data.** *Bioinformatics.* 2003; **19**(2): 295–6.
[PubMed Abstract](#) | [Publisher Full Text](#)
8. Xia J, Lyle NH, Mayer ML, *et al.*: **INVEX—a web-based tool for integrative visualization of expression data.** *Bioinformatics.* 2013; **29**(24): 3232–4.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
9. Heer J, Bostock M, Ogievetsky V: **D3: Data-Driven Documents.** *IEEE Trans Vis Comput Graph.* 2011; **17**(12): 2301–9.
[PubMed Abstract](#) | [Publisher Full Text](#)
10. Dryja TP, McGee TL, Reichel E, *et al.*: **A point mutation of the rhodopsin gene in one form of retinitis pigmentosa.** *Nature.* 1990; **343**(6256): 364–6.
[PubMed Abstract](#) | [Publisher Full Text](#)
11. Kent WJ, Sugnet CW, Furey TS, *et al.*: **The human genome browser at ucsc.** *Genome Res.* 2002; **12**(6): 996–1006.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
12. UniProt Consortium. **Update on activities at the universal protein resource (uniprot) in 2013.** *Nucleic Acids Res.* 2013; **41**(Database issue): D43–7.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
13. Boeckmann B, Blatter MC, Famiglietti L, *et al.*: **Protein variety and functional diversity: Swiss-Prot annotation in its biological context.** *C R Biol.* 2005; **328**(10–11): 882–99.
[PubMed Abstract](#) | [Publisher Full Text](#)
14. Punta M, Coghill PC, Eberhardt RY, *et al.*: **The Pfam protein families database.** *Nucleic Acids Res.* 2012; **40**(Database issue): D290–301.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
15. Yachdav G: **HeatMap Viewer.** *Zenodo.* 2014. [Data Source](#)

Open Peer Review

Current Peer Review Status:

Version 1

Reviewer Report 05 March 2014

<https://doi.org/10.5256/f1000research.3678.r3682>

© 2014 Ison J. This is an open access peer review report distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Jon C. Ison

EMBL European Bioinformatics Institute, Hinxton, Cambridge, UK

The article is very well written and tells a nice story, with compelling real-world examples. The software should have scientific impact by providing a convenient overview of matrix data, along the lines already suggested by the authors, and certainly by saving other scientist/developers the need to develop such functionality.

The software fulfills a need for an easy to use widget for heatmap rendering and there is no doubt that this is a valuable contribution to the BioJS collection. However, I believe It would help many readers if the article placed the software in the broader context of similar offerings, so it would be good if the article enumerated these, perhaps as some sort of "feature matrix"?

I appreciated the test server very much and encourage the authors to support this service in the future and further develop the functionality. Please note that examples of the CSV format are needed (at least I could not find them).

Competing Interests: No competing interests were disclosed.

I confirm that I have read this submission and believe that I have an appropriate level of expertise to confirm that it is of an acceptable scientific standard.

Reviewer Report 27 February 2014

<https://doi.org/10.5256/f1000research.3678.r3752>

© 2014 Deu-Pons J. This is an open access peer review report distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Jordi Deu-Pons

Biomedical Genomics Group, University Pompeu Fabra (UPF), Barcelona, Spain

This is an interesting article and piece of software. I think it contributes towards further alternatives to easily visualize high dimensionality data on the web. It's simple and easy to embed into other web frameworks or applications.

Minor revisions**a) About the software**

1 - CSV format. It was hard to guess the expected format. The authors need to add a syntax description of the CSV format at the help page.

2 - Simple HTML example. It will be easy to test HeatmapViewer (HmV) if you add a simple downloadable example file with the minimum required HTML-JavaScript to set up a HmV (without all the CSV import code).

3 - Color scale. HmV only implements a simple three point linear color scale. For me this is the major weakness of HmV. It will be very convenient that in the next HmV release the user can give as a parameter a function that manages the score to color conversion.

b) About the paper

1 - Introduction (4th paragraph): There are many alternatives to explore a dataset using heat maps. The author only cites two and it's not clear if you refer to "JavaScript" or "web" alternatives. I think that you have to emphasize the strengths of HmV in comparison to other alternatives (in my opinion, one strength is that it is a good lightweight alternative to embed heat maps in a web report). Example of alternatives that I know of (but I'm sure that there are many more) are:

- <http://www.broadinstitute.org/gsea> (desktop)
- <http://jheatmap.github.io/jheatmap/> (website)
- <http://www.gitools.org/> (desktop)
- <http://blog.nextgenetics.net/demo/entry0044/> (website)
- <http://docs.scipy.org/doc/numpy/reference/generated/numpy.histogram2d.html> (python)
- http://matplotlib.org/api/pyplot_api.html (python)

2 - Predicted protein mutability landscape: The authors say: "Without using a tool such as the HeatmapViewer, we could hardly obtain an overview of the protein mutability landscape". This paragraph seems to suggest that you can explore the data with HmV. I think that HmV is a good tool to report your data, but not to explore it.

3 - Conclusions: The authors say: "... provides a new, powerful way to generate and display matrix data in web presentations and in publications." To use heat maps in web presentations and publications is nothing new. I think that HmV makes it easier and user-friendly, but it's not new.

Competing Interests: No competing interests were disclosed.

I confirm that I have read this submission and believe that I have an appropriate level of expertise to confirm that it is of an acceptable scientific standard.

The benefits of publishing with F1000Research:

- Your article is published within days, with no editorial bias
- You can publish traditional articles, null/negative results, case reports, data notes and more
- The peer review process is transparent and collaborative
- Your article is indexed in PubMed after passing peer review
- Dedicated customer support at every stage

For pre-submission enquiries, contact research@f1000.com

F1000Research