Check for updates

RESEARCH NOTE

A biochemical logarithmic sensor with broad dynamic range

[version 1; peer review: 1 approved with reservations]

Steven A. Frank

Department of Ecology and Evolutionary Biology, University of California, Irvine, CA, 92697-2525, USA

V1 **First published:** 16 Feb 2018, 7:200
<https://doi.org/10.12688/f1000research.14016.1>
Second version: 23 Mar 2018, 7:200
<https://doi.org/10.12688/f1000research.14016.2>
Latest published: 18 Apr 2018, 7:200
<https://doi.org/10.12688/f1000research.14016.3>

Abstract

Sensory perception often scales logarithmically with the input level. Similarly, the output response of biochemical systems sometimes scales logarithmically with the input signal that drives the system. How biochemical systems achieve logarithmic sensing remains an open puzzle. This article shows how a biochemical logarithmic sensor can be constructed from the most basic principles of chemical reactions. Assuming that reactions follow the classic Michaelis-Menton kinetics of mass action or the more generalized and commonly observed Hill equation response, the summed output of several simple reactions with different sensitivities to the input will often give an aggregate output response that logarithmically transforms the input. The logarithmic response is robust to stochastic fluctuations in parameter values. This model emphasizes the simplicity and robustness by which aggregate chemical circuits composed of sloppy components can achieve precise response characteristics. Both natural and synthetic designs gain from the power of this aggregate approach.

Keywords

Biochemical circuit, Hill equation, synthetic biology, systems biology, aggregation, robustness

Open Peer Review

Approval Status

	1	2
version 3 (revision) 18 Apr 2018		
version 2 (revision) 23 Mar 2018	view	view
version 1 16 Feb 2018	view	

1. **Sudin Bhattacharya** , Michigan State University, East Lansing, USA
2. **Marco Archetti** , University of East Anglia, Norwich, UK

Any reports and responses or comments on the article can be found at the end of the article.

Corresponding author: Steven A. Frank (safrank@uci.edu)

Author roles: Frank SA: Conceptualization, Formal Analysis, Funding Acquisition, Investigation, Methodology, Project Administration, Resources, Software, Supervision, Validation, Visualization, Writing – Original Draft Preparation, Writing – Review & Editing

Competing interests: No competing interests were disclosed.

Grant information: National Science Foundation grant DEB-1251035 supports my research.

The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

Copyright: © 2018 Frank SA. This is an open access article distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

How to cite this article: Frank SA. **A biochemical logarithmic sensor with broad dynamic range [version 1; peer review: 1 approved with reservations]** F1000Research 2018, 7:200 <https://doi.org/10.12688/f1000research.14016.1>

First published: 16 Feb 2018, 7:200 <https://doi.org/10.12688/f1000research.14016.1>

Introduction

I present a simple biochemical circuit that logarithmically transforms input signals. This circuit adds the outputs of several reactions that follow standard mass action Michaelis-Menton kinetics. Alternatively, the biochemical kinetics may follow the commonly observed Hill equation response, which includes Michaelis-Menton kinetics as a special case. This sensor has high dynamic range, responding logarithmically across many orders of magnitude. The high dynamic range is achieved by adding together reactions with different sensitivity ranges. The aggregate nature of this circuit provides robustness to parameter variations. Aggregate sensor design may explain the commonly observed high dynamic range of logarithmic biological responses and may also provide a useful tool for synthetic biology.

Results and discussion

Many biochemical reactions and cellular responses transform an input, x , into an output, y , according to the Hill equation

$$y = \frac{x^k}{c^k + x^k},$$

in which c is the value of the input x that yields one-half of the maximal output response, k is the Hill coefficient that determines the shape of the response, and y is normalized to be between

0 and 1¹. Simple mass action kinetics often follows the Hill equation with $k = 1$, which corresponds to classical Michaelis-Menton kinetics². For example, the input may drive production of the output, and the output may spontaneously transform back to a prior state.

The output of the Hill equation scales approximately logarithmically with its input through the middle part of its response range, because y is roughly linear with respect to $\log x$. Prior studies have emphasized that a Hill equation response can act as a logarithmic sensor^{3,4}. However, a single Hill equation response provides a logarithmic sensor with limited dynamic range (Figure 1A).

My extended dynamic range sensor arises by adding together n Hill equations with increasing values of the half-maximal response, c_i , as

$$y = \sum_{i=0}^{n-1} \frac{x^k}{c_i^k + x^k}. \quad (1)$$

For example, if $c_i = b^i$, then each reaction in the sum has an increasing input value at which its maximal sensitivity occurs. Figure 1B–E shows that simple combinations of k and b create a logarithmic sensor, in which the output is linearly related to the

Figure 1. The logarithmic sensor response, y , from the sum of Hill equations given in Equation 1, versus the logarithm of the input, x , on a $\log_2$ scale. Each unit on the input scale corresponds to a doubling of the input. The range of 13 doublings is approximately four orders of magnitude, $2^{13} \approx 10^4$. A logarithmic sensor responds linearly with respect to the logarithm of the input. The solid blue lines show the response, y , from Equation 1. The dashed gold lines are linear fits to the response. (A) A single Hill equation with $c = 1$ and $k = 2$. A linear response with low sensitivity occurs over a few doublings at small input levels. The following plots all use $n = 7$ and additional parameters as described from the summed Hill equation in Equation 1, in which $c_i = b^i$. (B) Response with $k = 1$ and $b = 4$. (C) Response with $k = 2$ and $b = 4$. (D) Response with $k = 1$ and $b = 8$. (E) Response with $k = 2$ and $b = 8$. (F) Same average parameters values of $k = 2$ and $c_i = b^i$ for $b = 4$ as in the plot above, but with random parameter fluctuations around those average values. For each of the 7 Hill equations in the sum given in Equation 1, each parameter was obtained by a different random number drawn from a normal distribution. For each k , the parameters were drawn from a normal distribution with mean 2 and standard deviation $2 \times 0.25 = 0.5$. For each c_i , the parameters were drawn from a normal distribution with mean 4^i and standard deviation $4^i \times 0.25$. The response remains nearly linear in spite of the random parameter fluctuations.

logarithm of the input. The logarithmic relation holds robustly when the parameters k and b of the individual reactions vary stochastically (Figure 1F).

Several biochemical circuit responses and many aspects of perception scale logarithmically⁵. A robust and generic pattern of this sort seems likely to depend on a robust and generic underlying design. In the search for a generic circuit, my biochemical logarithmic sensor has three advantages over prior designs. First, prior models depended on particular molecular assumptions about biochemical kinetics or reaction pathways^{3,4}. My design requires only Michaelis-Menton or Hill equation responses, which are very widely observed in biochemical and cellular systems¹. Second, prior models focused on single input-output processes, which have relatively narrow dynamic range. My aggregate design provides a logarithmic response over a vastly greater range. Third, the prior models' responses are easily perturbed

by parameter fluctuations. My design performs robustly with respect to broad fluctuations in parameters. The robustness of my logarithmic sensor emphasizes the potential to achieve precise response characteristics from underlying sloppy components when using an aggregate design^{6,7}.

Competing interests

No competing interests were disclosed.

Grant information

National Science Foundation grant DEB-1251035 supports my research.

The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

References

1. Zhang Q, Bhattacharya S, Andersen ME: **Ultrasensitive response motifs: basic amplifiers in molecular signalling networks**. *Open Biol.* 2013; **3**(4): 130031.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
2. Frank SA: **Input-output relations in biological systems: measurement, information and the Hill equation**. *Biol Direct.* 2013; **8**: 31.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
3. Daniel R, Rubens JR, Sarpeshkar R, et al.: **Synthetic analog computation in living cells**. *Nature.* 2013; **497**(7451): 619–623.
[PubMed Abstract](#) | [Publisher Full Text](#)
4. Olsman N, Goentoro L: **Allosteric proteins as logarithmic sensors**. *Proc Natl Acad Sci U S A.* 2016; **113**(30): E4423–E4430.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
5. Adler M, Alon U: **Fold-change detection in biological systems**. *Curr Opin Syst Biol.* 2018; **8**: 81–89.
[Publisher Full Text](#)
6. Frank SA: **The common patterns of nature**. *J Evol Bio.* 2009; **22**(8): 1563–1585.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
7. Frank SA: **Evolution of robustness and cellular stochasticity of gene expression**. *PLoS Biol.* 2013; **11**(6): e1001578.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)

Open Peer Review

Current Peer Review Status: ?

Version 1

Reviewer Report 19 March 2018

<https://doi.org/10.5256/f1000research.15234.r30929>

© 2018 Bhattacharya S. This is an open access peer review report distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

? **Sudin Bhattacharya**

Department of Biomedical Engineering, Department of Pharmacology & Toxicology, Institute for Quantitative Health Science and Engineering, Michigan State University, East Lansing, MI, USA

The author presents an interesting model of a robust biochemical logarithmic switch with a broad dynamical range as a sum of multiple Hill-equation based models.

1. My main problem with this work is the lack of a biological context with a real example (the author argues the model applies to natural as well as artificial circuits). Is the author proposing that the successive Hill-type switches would be arranged in series? A more natural example would be a layered cascade like a MAP kinase cascade¹. But in that case the output would not be a simple linear sum as in the author's Eqn. (1), but rather something like a Hill function of a Hill function.
2. The contention that "My design performs (more) robustly with respect to broad fluctuations in parameters" should be established more rigorously. How were the stochastic simulations performed? It's hard to tell since no methodological details are provided.
3. "Menten" in Michaelis-Menten mis-spelt throughout manuscript (after Maud Menten: https://en.wikipedia.org/wiki/Maud_Menten)

References

1. Huang CY, Ferrel JE: Ultrasensitivity in the mitogen-activated protein kinase cascade. *Proceedings of the National Academy of Sciences*. 1996; **93**: 10078-10083

Is the work clearly and accurately presented and does it cite the current literature?

Yes

Is the study design appropriate and is the work technically sound?

No

Are sufficient details of methods and analysis provided to allow replication by others?

Partly

If applicable, is the statistical analysis and its interpretation appropriate?

Partly

Are all the source data underlying the results available to ensure full reproducibility?

Yes

Are the conclusions drawn adequately supported by the results?

No

Competing Interests: No competing interests were disclosed.

Reviewer Expertise: Computational biology and toxicology

I confirm that I have read this submission and believe that I have an appropriate level of expertise to confirm that it is of an acceptable scientific standard, however I have significant reservations, as outlined above.

Author Response (F1000Research Advisory Board Member) 19 Mar 2018

Steven Frank, Department of Ecology & Evolutionary Biology, University of California, Irvine, USA

I thank Dr. Bhattacharya for sharing his expertise on topics related to the important Hill equation (see ref. 1 of the article). Dr. Bhattacharya made three helpful comments in his review, which I respond to in reverse order.

First, I appreciate the spelling correction. I had reread the interesting history of the Michaelis-Menten equation when preparing this article, but nonetheless incorrectly spelled Menten's name. I have fixed that misspelling in the revision.

Second, I have uploaded the source code, as a supplementary file, that I used to do the stochastic simulations. The short, simple code provides a clear, exact description of the methods. The code was used to generate Figure 1, and can be used to regenerate that figure and explore alternative assumptions. A summary of the methods are provided in the legend for Figure 1.

The final point concerns the lack of specific biological examples and details. The first aspect of this comment is a question asked by Dr. Bhattacharya: "Is the author proposing that the successive Hill-type switches would be arranged in series?"

I am proposing a summation of individual responses to a stimulus, as described in Equation 1. For example, suppose that a set of sensors respond to sound intensity. Each sensor has a Hill-like response curve, but tuned to different intensity level. The output of the aggregate set of sensors is the sum of the individual sensor responses. Each sensor may comprise a

simple or complex set of reactions. All that we care about here is that the net response per sensor is Hill-like in shape.

That same logic could describe the response to a molecular signal. Various reactions could each have a Hill equation response, but tuned to different sensitivities. The aggregate consequence of those responses would be a net output level.

With regard to an explicit example, I gave a lot of thought to that issue while preparing the manuscript. I could not find a compelling example for which sufficient biological detail about mechanism had been described. There are plausible cases that are worth exploring, such as the sensory problems that I mentioned. For molecular systems, there are hormones for which cells have multiple receptors, presumably tuned differently with regard to response and other aspects (e.g., estrogen receptors). However, I agree that those multireceptor systems do not provide a compelling case given current knowledge.

Why are there no compelling molecular examples? I think the reason is that researchers rarely look for responses that arise by aggregate processes, such as summation of underlying reactions. Instead, the search is almost always for a single reaction or explicit pathway that exactly matches the desired input-output pattern. So my goal for this article is to suggest a plausible alternative for consideration.

One advantage of publishing with F1000Research is that I can update the article in the future. If a good example arises in discussion with readers of the article or from the literature, I will update the article to include that example. For now, I think it is most important that the novel idea be published in a concise and direct manner, with emphasis on the simple logic of the model.

Competing Interests: No competing interests were disclosed.

The benefits of publishing with F1000Research:

- Your article is published within days, with no editorial bias
- You can publish traditional articles, null/negative results, case reports, data notes and more
- The peer review process is transparent and collaborative
- Your article is indexed in PubMed after passing peer review
- Dedicated customer support at every stage

For pre-submission enquiries, contact research@f1000.com

F1000Research