SOFTWARE TOOL ARTICLE

A multi-spectral myelin annotation tool for machine learning based myelin quantification [version 1; peer review: 1 not approved]

Abdulkerim Çapar ^{1,2}, Sibel Çimen ³, Zeynep Aladağ⁴, Dursun Ali Ekinci^{1,2}, Umut Engin Ayten³, Bilal Ersen Kerman ^{4,5}, Behçet Uğur Töreyn ¹

¹Informatics Institute, Istanbul Technical University, Istanbul, 34469, Turkey

²Argenit Akıllı Bilgi Teknolojileri, Istanbul, 34469, Turkey

³Department of Electronics and Communication Engineering, Yıldız Technical University, Istanbul, 34220, Turkey

⁴Regenerative and Restorative Medicine Research Center, Istanbul Medipol University, Istanbul, 34810, Turkey

⁵School of Medicine Department of Histology and Embryology, Istanbul Medipol University, Istanbul, 34810, Turkey

V1 First published: 21 Dec 2020, 9:1492
<https://doi.org/10.12688/f1000research.27139.1>
 Second version: 09 Mar 2022, 9:1492
<https://doi.org/10.12688/f1000research.27139.2>
 Latest published: 27 Apr 2022, 9:1492
<https://doi.org/10.12688/f1000research.27139.3>

Abstract

Myelin is an essential component of the nervous system and myelin damage causes demyelination diseases. Myelin is a sheet of oligodendrocyte membrane wrapped around the neuronal axon. In the fluorescent images, experts manually identify myelin by co-localization of oligodendrocyte and axonal membranes that fit certain shape and size criteria. Because myelin wriggles along x-y-z axes, machine learning is ideal for its segmentation. However, machine-learning methods, especially convolutional neural networks (CNNs), require a high number of annotated images, which necessitates expert labor. To facilitate myelin annotation, we developed a workflow and a software for myelin ground truth extraction from multi-spectral fluorescent images. Additionally, we shared a set of myelin ground truths annotated using this workflow.

Keywords

myelin annotation tool, myelin quantification, fluorescence images, machine learning, image analysis

Open Peer Review

Approval Status

	1	2
version 3		
(revision)		
27 Apr 2022		
version 2		
(revision)		
09 Mar 2022		
version 1		
21 Dec 2020		

1. **Predrag Janjic**, Macedonian Academy of Sciences and Arts, Skopje, North Macedonia
2. **Mustafa Ozuysal**, Macedonian Academy of Sciences and Arts, Skopje, North Macedonia

Any reports and responses or comments on the article can be found at the end of the article.

This article is included in the **NEUBIAS - the Bioimage Analysts Network** gateway.

This article is included in the **Artificial Intelligence and Machine Learning** gateway.

Corresponding authors: Bilal Ersen Kerman (bekerman@medipol.edu.tr), Behçet Uğur Töreyn (toreyin@itu.edu.tr)

Author roles: **Çapar A:** Methodology, Project Administration, Software, Writing – Review & Editing; **Çimen S:** Formal Analysis, Investigation, Visualization, Writing – Original Draft Preparation; **Aladağ Z:** Investigation, Visualization; **Ekinci DA:** Formal Analysis, Writing – Review & Editing; **Ayten UE:** Methodology, Writing – Review & Editing; **Kerman BE:** Funding Acquisition, Methodology, Project Administration, Validation, Writing – Original Draft Preparation, Writing – Review & Editing; **Töreyn BU:** Methodology, Writing – Review & Editing

Competing interests: No competing interests were disclosed.

Grant information: Funding for this work was provided by TUBITAK (316S026).

The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

Copyright: © 2020 Çapar A *et al.* This is an open access article distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

How to cite this article: Çapar A, Çimen S, Aladağ Z *et al.* **A multi-spectral myelin annotation tool for machine learning based myelin quantification [version 1; peer review: 1 not approved]** F1000Research 2020, 9:1492
<https://doi.org/10.12688/f1000research.27139.1>

First published: 21 Dec 2020, 9:1492 <https://doi.org/10.12688/f1000research.27139.1>

Introduction

Myelin degeneration causes neurodegenerative disorders, such as multiple sclerosis (MS)^{1,2}. There are no remyelinating drugs. Myelin quantification is essential for drug discovery, which often involves screening thousands of compounds³. Currently, myelin quantification is manual, and labor-intensive. Automation of quantification using machine learning can facilitate drug discovery by reducing time and labor costs. However, myelin annotation suffers the same limitations as manual quantification. To assist researchers and bioimage analysts, we developed a workflow and a software for myelin ground truth extraction from multi-spectral fluorescent images.

Myelin is formed by oligodendrocytes wrapping the axons⁴. It is identified by continuous co-localization of cellular extensions that span multiple channels and z-sections (Figure 1). In our workflow, co-localizing pixels, candidate myelins, were determined using Computer-assisted Evaluation of Myelin (CEM) software that we previously developed⁵. In the current study, the 3D Myelin Marking (CEM3D) tool⁶ was developed to efficiently evaluate these candidate myelins and to extract myelin ground truths. Using CEM3D, an RGB-composite z-section image, corresponding CEM output image, and expert's markings can be visualized simultaneously to decide whether to keep or remove candidate pixels (see *Implementation*). The user can move along x-y-z axes and show/hide channels, images and markings. Markings from the -1/+1 z-sections can be viewed simultaneously. Finally, CEM3D allows simultaneous visualization of myelin markings of two experts, which is important for inter-expert comparison.

Using the described workflow, we annotated five images encompassing approximately 2×8 mm by 30–50 μ m volume. The entire process, which would have taken several weeks, took approximately 5 days. More than 30,000 feature images were extracted from these five images and were used for testing various machine-learning methods^{7–9}. The annotated images, which are available with the manuscript, are a resource for the researchers working not only on myelin detection but also on segmenting multi-spectral images.

Methods

Image acquisition

Images were previously acquired⁵. Briefly, co-cultures of mouse embryonic stem cell-derived oligodendrocytes and neurons were grown in microfluidic chambers. After myelin formation, cells were fixed in paraformaldehyde and were stained with 1:1,000 mouse or rabbit anti-TUJ1 (Covance), 1:50 rat anti-MBP (Serotec) and DAPI (Sigma). Images were acquired on Zeiss LSM 710 or 780 confocal microscopes as 10% overlapping tiles encompassing the entire myelination chamber. The z-axis, 30–50 μ m, was covered by 1- μ m-thick optical z-sections. The tiles were stitched together on Zen software (Zeiss). These images are available from the Image Data Resource¹⁰.

Implementation

In CEM3D, a new project is started by loading oligodendrocyte, axon, and nucleus images, red, green, and blue channels respectively in the example (Figure 2). Optionally, candidate myelin image, which is converted to vectors using the included module (see below), is loaded. Users can save and reopen

Figure 1. An example of multi-spectral fluorescent image. 20x confocal microscopy image tiles were stitched together covering approximately 2×8 mm by 30–50 μ m volume. Boxed area is enlarged to show myelin (brackets) and the false positive pixels (circles).

projects. In CEM3D, users can zoom using the mouse wheel and can move in the x-y axes and z-axis using scroll bars and buttons respectively (Figure 2 and Figure 3).

Myelin pixels may be marked at various thickness values (Figure 3). CEM3D records myelin drawings as vectors in the “.iev” files. These vectors can be modified or deleted in CEM3D

Figure 2. Starting a new project in CEM3D. Buttons for loading oligodendrocyte, axon, and nucleus images, and navigating the z-stack button to up and down are marked.

Figure 3. Myelin drawing and saving in CEM3D. The relevant buttons and myelin vectors are marked.

(Figure 3). Optionally, to facilitate myelin detection, the candidate myelins, can be loaded from CEM. Myelin identification using CEM is described in detail in 5. Output of CEM is a binary image, which is converted to vectors using the included module (Figure 4). Note that the conversion will overwrite your existing myelin vectors.

Additionally, CEM candidate myelins or two experts' myelin vectors can be visualized. First, rename and copy the .iev file containing second myelin vectors to the same folder. Next, modify the .ini files as shown in Figure 5. After loading the modified .ini file using 'Merge Edit' button, myelin vectors will be shown in two different colors (Figure 6). These vectors can be modified as in Figure 6.

Once done with marking, users can convert the myelin vectors into an image using the "Save Myelin Mask Image" button. We implemented this strategy to extract gold standard myelin ground truths.

Comparative analysis

The myelin marked by two experts were compared against the gold standards. Experts' precision for each image was calculated as described in 8. The average precision was calculated as mean of precision values of each expert for each image.

Operation

CEM3D is written in Pascal with the Delphi XE5 platform. The program can be run on 64-bit Microsoft Windows operating systems.

Results

In this study, myelin was marked by two experts on previously acquired oligodendrocyte and neuron co-culture images⁵ using the described workflow (see *Implementation*). A third expert evaluated their markings and extracted gold standard myelin ground truths. The ground truth images were saved as TIF on CEM3D⁶. All images are available (see below).

Because each image covered a large volume (approximately 2 x 8 mm by 30–50 μm), the entire process took approximately five work days. We estimated that it would have taken several weeks using conventional methods. Thus, CEM3D enabled collaboration of three experts for accelerated myelin ground truth extraction.

Next, we calculated experts' performance. When compared to the gold standards that we extracted, two experts averaged 48.39% precision. The highest precision of an expert was 87.95% for one image. In comparison, our customized-CNN and Boosted Trees consistently reached precision values over

Figure 4. Loading CEM output image. To load candidate myelin pixels, use "Convert Binary Image to Vector" button.

Figure 5. Visualizing two myelin vectors simultaneously. Modify .ini file as in the lower panels and load it using “Merge Edit” button.

Figure 6. Modifying the myelin vectors. CEM candidate myelins or two experts' markings can be shortened, deleted or drawn over.

99%⁸. These results suggest that, machine learning methods can outperform human annotators once trained with accurately labeled data.

Conclusion

CEM3D⁶ accelerates annotation of multi-spectral images. As an example, we used it to annotate myelin, which can only be identified as co-localization of neuron and oligodendrocyte membranes within certain criteria. CEM3D's visualization features simplified inter-expert collaboration and validation. Moreover, myelin ground truths accompanying this manuscript are a resource for the researchers working on segmenting myelin as well as other features in multi-spectral images.

Data availability

Underlying data

Image Data Resource: A Multi-Spectral Myelin Annotation Tool for Machine Learning Based Myelin Quantification. Project number idr0100; <https://doi.org/10.17867/10000152>¹⁰.

This project contains the raw image files analyzed in this article.

Data are available under the terms of the [Creative Commons Attribution 4.0 International license](#) (CC-BY 4.0).

Software availability

CEM and CEM3D are available from: <https://github.com/ArgenitTech/Neubias>.

Archived source code as at the time of publication: <https://doi.org/10.5281/zenodo.4108321>⁶.

License: [Non-Profit Open Software License 3.0](#) (NPOSL-3.0).

Acknowledgements

This publication was supported by COST Action NEUBIAS (CA15124), funded by COST (European Cooperation in Science and Technology).

References

1. Aydinli Fİ, Çelik E, Vatandaşlar BK, et al.: **Myelin disorders and stem cells: as therapies and models**. *Turk J Biol*. 2016; **40**: 1068–1080.
[Publisher Full Text](#)
2. Reich DS, Lucchinetti CF, Calabresi PA: **Multiple sclerosis**. *N Engl J Med*. 2018; **378**(2): 169–180.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
3. Cole KLH, Early JJ, Lyons DA: **Drug discovery for remyelination and treatment of MS**. *Glia*. 2017; **65**(10): 1565–1589.
[PubMed Abstract](#) | [Publisher Full Text](#)
4. Simons M, Nave KA: **Oligodendrocytes: Myelination and axonal support**. *Cold Spring Harb Perspect Biol*. 2015; **8**(1): a020479.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
5. Kerman BE, Kim HJ, Padmanabhan K, et al.: **In vitro myelin formation using embryonic stem cells**. *Development*. 2015; **142**(12): 2213–2225.
[PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
6. Argenit: **ArgenitTech/Neubias: 1.0.0.0 (Version 1.0.0.0)**. *Zenodo*. 2020.
<http://www.doi.org/10.5281/zenodo.4108321>
7. Çimen S, Çapar A, Ekinci DA, et al.: **DeepMQ: A deep learning approach based myelin quantification in microscopic fluorescence images**. In *European Signal Processing Conference, EUSIPCO*. 2018; 61–65.
[Publisher Full Text](#)
8. Yetiş SÇ, Çapar A, Ekinci DA, et al.: **Myelin Detection in Fluorescence Microscopy Images Using Machine Learning**. *J Neurosci Methods*. 2020; **346**: 108946.
[PubMed Abstract](#) | [Publisher Full Text](#)
9. Yetiş SÇ, Ekinci DA, Ertan Ç, et al.: **Myelin segmentation in fluorescence microscopy images**. In: *TİPTEKNO 2019 - Tıp Teknolojileri Kongresi* (Institute of Electrical and Electronics Engineers Inc., 2019). 2019.
[Publisher Full Text](#)
10. Capar A, Cimen Yetis S, Aladag Z, et al.: **Multi-Spectral Myelin Annotation Tool for Machine Learning Based Myelin Quantification**. *Image Data Resource*. 2020; project number 1451.
[Reference Source](#)

Open Peer Review

Current Peer Review Status:

Version 1

Reviewer Report 08 February 2021

<https://doi.org/10.5256/f1000research.29981.r76521>

© 2021 Janjic P. This is an open access peer review report distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Predrag Janjic

Research Center for Computer Science and Information Technology, Macedonian Academy of Sciences and Arts, Skopje, North Macedonia

The manuscript introduces a 3D extension of myelin annotation tool reported in Ref[5], now applicable to fluorescent stacks. Although the main rationale to develop an automated tool for producing ground truth images is clear, and the importance has been laid out, methodological details and comparative data are missing for a researcher dealing with myelin imaging to get an idea of what the tool is really computationally doing in order to decide on its practical utility.

Please rework the Introduction and despite rather harsh length constraints add some minimal description of what algorithms in Ref[5] do.

Image acquisition:

- Extend on the image and image processing details like the size of the captures, pixel size, deconvolving or not, depth corrections (you have some of it in the Results).

Implementation:

- Please extend on what has been done to integrate CEM tool, and parallel visualization of myelin in subsequent planes, figures Fig.5 and Fig.6., elaborating the utility of this step which is the main procedural added value of the presented tool. Please move to additional material or remove Fig.1 - Fig.4., which are more of a user guide and are disruptive in the value presentation.

Comparative analysis:

- Some more data is needed, new or from Ref[8] for a reader to be able to get the overall impression. Please consider adding a *Benchmarking* paragraph where you would extend a bit on some benchmarking given within the Results, with an estimate (table) of the computational time needed for the CEM scope per slice, and the total time to process a whole stack, all in order a potential end user to get an impression of the effort needed.

Results:

- Please extend on limitations & issues of the CEM3D, and try to estimate if possible specific performance over a whole stack using this extension. (which is the actual improvement and a gain compared to relying only on CEM).

Is the rationale for developing the new software tool clearly explained?

Yes

Is the description of the software tool technically sound?

No

Are sufficient details of the code, methods and analysis (if applicable) provided to allow replication of the software development and its use by others?

No

Is sufficient information provided to allow interpretation of the expected output datasets and any results generated using the tool?

Partly

Are the conclusions about the tool and its performance adequately supported by the findings presented in the article?

Partly

Competing Interests: No competing interests were disclosed.

Reviewer Expertise: computational neuroscience, structural studies of white matter, dynamical models of glial membrane.

I confirm that I have read this submission and believe that I have an appropriate level of expertise to state that I do not consider it to be of an acceptable scientific standard, for reasons outlined above.

Author Response 23 Feb 2022

Bilal Kerman

We thank Predrag Janjic for his helpful comments. We believe that we address his concerns and the updated manuscript is easier to read and more satisfactory to the readers. Please see our point by point responses below.

I apologize in the time it took us to update the manuscript. I moved between institutions and it took me a long time to settle in part due to the pandemic restrictions.

The manuscript introduces a 3D extension of myelin annotation tool reported in Ref[5], now applicable to fluorescent stacks. Although the main rationale to develop an automated tool for producing ground truth images is clear, and the importance has been laid out, methodological details and comparative data are missing for a researcher dealing with myelin imaging to get an idea of what the tool is really

computationally doing in order to decide on its practical utility.

Please rework the Introduction and despite rather harsh length constraints add some minimal description of what algorithms in Ref[5] do.

Response 1: We updated the Introduction to include: "In this context, CEM software functions as a candidate myelin detection program because it simply identifies overlapping pixels. Briefly, CEM removes cell bodies, defined as the overlap of nuclei and cellular marker, and identifies overlapping pixels between remaining oligodendrocyte and neuron channels⁶."

Image acquisition:

Extend on the image and image processing details like the size of the captures, pixel size, deconvolving or not, depth corrections (you have some of it in the Results).

Response 2: The tool described in this publication is not an image processing tool per se. Its main function is annotation of myelin pixels for machine learning studies. Therefore, in this revision, to prevent any confusion, we renamed the tool as CEMotate.

Implementation:

Please extend on what has been done to integrate CEM tool, and parallel visualization of myelin in subsequent planes, figures Fig.5 and Fig.6., elaborating the utility of this step which is the main procedural added value of the presented tool. Please move to additional material or remove Fig.1 - Fig.4., which are more of a user guide and are disruptive in the value presentation.

Response 3: In this study, the CEM tool is not integrated directly to CEMotate. We used images previously processed by CEM and annotated them using CEMotate. The details of processing by CEM were given in the reference Kerman et al. 2015. The one major goal of this manuscript is to introduce our myelin annotation tool and to describe how to utilize it. Therefore, we believe that Fig. 1 – Fig. 4. are useful for readers.

Comparative analysis:

Some more data is needed, new or from Ref[8] for a reader to be able to get the overall impression. Please consider adding a Benchmarking paragraph where you would extend a bit on some benchmarking given within the Results, with an estimate (table) of the computational time needed for the CEM scope per slice, and the total time to process a whole stack, all in order a potential end user to get an impression of the effort needed.

Response 4: The updated text below:

We added information on benchmarking and compared the length of the time it takes to use different approaches.

Results Section – Paragraph 2: Each image covered a large volume (approximately 2 x 8 mm by 30-50 μ m). While CEM determined the candidate myelins on five images in approximately 43 minutes, ML approach took only 1.04 seconds for the same process⁸ (Table 1). Extracting the gold standard myelin ground truths from five images with candidate pixels that were determined by CEM took approximately another 35 hours for one expert. This process involved determining FPs and FNs on ImageJ. The same process took approximately 20 hours for an expert using CEMotate. Thus, over 40% of time was saved (Table 2). Moreover, CEMotate enabled collaboration of three experts for accelerated myelin ground truth extraction. Because ImageJ does not have such a feature, we could not directly compare the times saved for this process.

Table 1. Time comparison to detect myelin in five images for CEM and ML Approach

CEM
ML Approach⁹

Time (~)
43 min
1.04 sec

Table 2. Time comparison for ImageJ and CEMotate annotation

ImageJ
CEMotate

Time (~)
35 hours
20 hours

CEM identified 219032 candidate myelin pixels on five images. Two experts identified TP myelins. A third expert evaluated these results to obtain the gold standard myelin ground truths which covered 9550 pixels. To the best of our knowledge, this is the first time myelin ground truths are shared with the science community.

Table 3. Experts' average precisions on candidate myelin pixels of five images

Expert 1
Expert 2

Average Precisions
36.23%
60.54%

Next, we calculated each expert's performance. Two experts averaged 48.39% precision. The highest precision of an expert was 87.95% for one image. In comparison, our customized-CNN and Boosted Trees consistently reached precision values over 99%⁸. These results suggest that machine learning methods can outperform human annotators once trained with accurately labeled data.

Results:

Please extend on limitations & issues of the CEM3D, and try to estimate if possible specific performance over a whole stack using this extension. (which is the actual improvement and a gain compared to relying only on CEM).

We updated the Results section to include the metrics as described above.

Competing Interests: No competing interests were disclosed.

The benefits of publishing with F1000Research:

- Your article is published within days, with no editorial bias
- You can publish traditional articles, null/negative results, case reports, data notes and more
- The peer review process is transparent and collaborative
- Your article is indexed in PubMed after passing peer review
- Dedicated customer support at every stage

For pre-submission enquiries, contact research@f1000.com

F1000Research